



8-TR TREADMILL

BASE FEATURES

DECK SYSTEM	Reversible MDF deck with phenolic coating
RUNNING BELT SYSTEM	22in (55cm) wide belt
SIZE OF RUNNING SURFACE	60in x 22in (152cm x 55cm)
ABSORPTION SYSTEM	Triple cell cushioning system provides maximum shock absorption making the entire deck a sweet spot
STEP UP HEIGHT	10in (25cm)
INCLINE RANGE	0-15% max incline
SPEED RANGE	0.5-12.5mph (0.5-20kmh)
HEART RATE MEASUREMENT SYSTEM	Telemetry and contact HR, Bluetooth w/19" display option
CENTER CONTROLS BAR	Warm bar with contact HR and Emergency Stop
DISPLAY	Choose from LCD, 10" or 19" OpenHub display options
USER DETECT SYSTEM	Yes, programmable on/off
ACCESSORIES	Multiple bottle and accessory holders, LCD and 10" displays pre-wired for 8 Series PVS entertainment, 800/900MHz receivers, and tablet holder
MAX USER WEIGHT	500lb (227kg)
DRIVE SYSTEM	5 HP AC motor
ELECTRICAL REQUIREMENTS	110V/20 Amp dedicated circuit with NEMA 5-20 outlet; or 220V/15 Amp dedicated circuit with NEMA 6-15 outlet
ADDITIONAL FEATURES	3.5in rollers

FRAME

MATERIAL	Powder Coated Steel Frame
CUSTOMIZABLE	Paint color options approval required
STANDARD COLOR OPTIONS	Star Trac Silver
LENGTH	81in (206cm)
WIDTH	32in (81cm)
HEIGHT	63in (160cm)
NET WEIGHT	425lb (193kg)
SHIPPING DIMENSIONS	84in x 36in x 31in (214cm x 90cm x 80cm)
SHIPPING WEIGHT	499lbs (227kg)

ADDITIONAL SKUS

9-9191-8TR-110-LCD, 9-9194-8TR-220CE-LCD, 9-9192-8TR-220UL-LCD, 9-9191-8TR-110-10, 9-9191-8TR-220CE-10, 9-9191-8TR-110-19-ATSC, 9-9192-8TR-220UL-19-ISDB-DMB-PAL, 9-9194-8TR-220CE-19-ISDB-DMB-PAL, 9-9194-8TR-220CE-19-ISDB-DMB-PAL